

WORK MATERIAL	NON-ALLOY STEELS		ALLOY STEELS		SOFT GREY CAST IRON		HARD GREY CAST IRON	
STRENGTH	< 700 N/mm ²		< 1000 N/mm ²		< HB240, GG25		< HB300, GG40	
DRILLING SPEED	Ø1.0 ~ Ø2.9 : 50 ~ 100 m/min Ø3.0 ~ : 130 ~ 150 m/min		Ø1.0 ~ Ø2.9 : 40 ~ 90 m/min Ø3.0 ~ : 115 ~ 135 m/min		Ø1.0 ~ Ø2.9 : 80 ~ 160 m/min Ø3.0 ~ : 230 ~ 250 m/min		Ø1.0 ~ Ø2.9 : 50 ~ 100 m/min Ø3.0 ~ : 140 ~ 160 m/min	
DIAMETER	N	S	N	S	N	S	N	S
1.0	16250	0.05	14800	0.05	26600	0.05	17300	0.05
2.0	16250	0.07	14800	0.07	26600	0.07	17300	0.07
3.0	16000	0.16	14500	0.16	26000	0.16	17000	0.16
4.0	12000	0.17	11000	0.17	20000	0.17	13000	0.17
5.0	9550	0.18	8600	0.18	16000	0.18	10000	0.18
6.0	8000	0.20	7200	0.20	13000	0.20	8500	0.20
7.0	6800	0.22	6100	0.22	11500	0.22	7300	0.22
8.0	6000	0.24	5400	0.24	9900	0.24	6400	0.24
9.0	5300	0.27	4800	0.27	8800	0.27	5700	0.27
10.0	4800	0.30	4300	0.30	8000	0.30	5100	0.30
12.0	4000	0.33	3600	0.33	6600	0.33	4250	0.33
14.0	3400	0.36	3050	0.36	5700	0.36	3650	0.36
16.0	3000	0.39	2700	0.39	5000	0.39	3200	0.39
18.0	2650	0.42	2400	0.42	4400	0.42	2850	0.42
20.0	2400	0.45	2150	0.45	4000	0.45	2550	0.45

▶ Recommend to reduce the feed rate as following

Feed 100% : DH406(3×D)

Feed 85% : DH408(5×D)

Feed 70% : DH421(8×D)

N = R.P.M

S = Feed per Revolution (mm/rev.)